

## Attachment J.3.2

<b>Environment</b>	The lift structure and doors are to be protected from rain by glass panels on the external wall side.
<b>Technical Compliance</b>	<ul style="list-style-type: none"> <li>• Host country's local building codes, including zoning requirements</li> <li>• OBO 2015 design standards.</li> </ul>
<b>Number of stops</b>	Two (2)
<b>Number of Entrances</b>	Two (2) Inline
<b>Capacity (Kg)</b>	5 Passengers / 410 Kg
<b>Travel (mm)</b>	2,825mm approx.
<b>Lifting speed (m/s)</b>	0.15 m/s
<b>Platform finish</b>	<ul style="list-style-type: none"> <li>• Full height wall on one side</li> <li>• Floor in vinyl</li> <li>• Stainless Steel Face Plate</li> <li>• Stainless Steel Handrail</li> </ul>
<b>Operating panel</b>	Horizontal COP
<b>Type of shaft</b>	<p>Steel structure finished in powder spray standard color white RAI 9003</p> <p>Shaft ceiling with LED lights</p> <p>One side of structure (facing garden) to be clear glass panels.</p>
<b>Structural opening dimensions (mm)</b>	1,305mm wide x 1,630mm deep
<b>Doors design and type</b>	<p>Double hinged glass doors with safety clear glass windows.</p> <p>Steel door and frame finished in spray color white</p>

## Attachment J.3.2

	RAL9003
<b>Doors clear dimensions</b>	914mm x 2,032mm (Other dimensions will need approval by the COR.)
<b>Doors opener mechanism</b>	Hidden internal door closer with single operated swing doors
<b>Elevator controls</b>	Electronically controlled
<b>Operating voltage</b>	400V, 3-Phase, 50hz
<b>Features (included)</b>	<ul style="list-style-type: none"><li>• Interlocked entrance doors</li><li>• Call and Send functionality</li><li>• Manual emergency lowering</li><li>• Battery operated emergency lowering</li><li>• External alarm sounder</li><li>• Self-Support Structure with 25mm thick panels</li><li>• Auto dialer communication</li><li>• Soft Start</li></ul>
<b>Equipment Warranty</b>	24 months from commissioning